

719 century ave sw • grand rapids, mi 49503 p. 616.369.0522 e. info@flooralytics.com



certificate of testing

client	Aquaclean USA Inc.
	834 Huffman Street
	Greensboro, NC 27405
product identification	LIDO – AC-SF-GRS

test method performed	standard methods of tests and classification system for cigarette ignition resistance of components of upholstered furniture nfpa 260 – 2019: cover fabrics test
date of test	5.15.2023

test results

specimen	char length
	(in.)
1	0.6
2	0.6
3	0.6

notes

test conditions	70 ±3.5°f, 50 ±5% relative humidity
ignition source	srm1196a
sampling	as received

acceptance criteria

- class i test specimen exhibits no ignition of any test assembly, vertical char length on any of the three specimens does not exceed 45mm (1.8 inches)
- class ii test specimen exhibits ignition of test assembly and / or char length of any of the three specimens exceeds 45mm (1.8 inches)

classification

based upon the test results and acceptance criteria listed above, the product identified is

🛛 class i

🗆 class ii

certification statement by signing below, the lab certifies that the results were obtained after testing specimens submitted by the client in accordance to the procedures and equipment specified by the standard stated above.



This report is confidential and prepared for the exclusive use of the client to whom they are addressed. It may not be reproduced or published without prior written approval. The results apply only to the samples tested may not necessarily reflect product performance under actual use. The results are representative of similar goods only to the extent that the sample tested is representative of those goods.