

Maxwell Road
Stevenage
Hertfordshire
SG1 2EW

T: +44(0) 1438 777 700
info@fira.co.uk

www.fira.co.uk

Interfabrics SI

Carretera De Alicante, 76
03801 Alcoy
Spain

Our Ref: **TFFLF89036**

Date: 01 October 2019

Delivery Date: 20 September 2019

Test Dates: 24-30 September 2019

For the attention of Amaya Castello

SAMPLE(S) FOR TEST:



One, Fabric – Ref: PANDORA-AC-FR

Note: The above descriptions are as supplied by the client and have not been verified by FIRA International who can take no responsibility for the accuracy of the description.

TEST REQUIREMENTS:

Schedule 4 Part I (based on BS 5852: 1979 Part 1)*
Schedule 5 Part I (based on BS 5852: 1979 Part 1)

RESULT:

Pass- P0
Pass- P1

The material was subjected to the water soak procedure and line dried as detailed in The Furniture and Furnishings (Fire) (Safety) Regulations 1988, amended 1989, 1993 and 2010.

FIRA International is a UKAS TESTING Laboratory No. 0174

Tests marked "Not UKAS Accredited" in this Report are not included in the UKAS Accreditation Schedule for our laboratory.

Technical report references marked * indicate this report is supplementary to the previous report with the same reference.

Opinions and interpretations expressed herein are outside the scope of UKAS Accreditation.

This Report relates to the sample(s) submitted for test and no others. Additions, deletions or alterations are not permitted.

Test reports are given to the client in confidence, and may only be reproduced in whole or in part with written permission from FIRA International Limited. Note that the words "tested by FIRA International" may be used in subsequent publicity for the product; "approved" must **not** be used.

Tests are carried out on the understanding that neither FIRA International Limited nor its officers can accept any legal responsibility for information or advice given or opinions expressed whether in response to specific enquiries or otherwise. This Report is given subject to the Terms of Business of FIRA International Limited which are available at <https://www.fira.co.uk/images/FIRA-International-Limited-Standard-Terms-of-Business-2018.pdf>

*The test was carried out using commercially available cigarettes which deviate from the specifications stated in BS 5852: Part 1: 1979 as used for Schedule 4 of the Regulations. Although these cigarettes do not fully meet the specifications laid down in BS 5852: Part 1 this is regarded as having no significant effect on the test.



TECHNICAL REPORT

DESCRIPTION

Enquiry No: TFFLF89036

Item: One, Fabric – Ref: PANDORA-AC-FR

Supplied by: Interfabrics SI

The following test results relate only to the ignitability of the combination of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.

FURNITURE AND FURNISHINGS (FIRE) (SAFETY) REGULATIONS 1988 - AMENDED 1989, 1993 AND 2010 **SCHEDULE 4 PART 1 MODIFICATION TO BS 5852: PART 1 THE CIGARETTE TEST**

Initial Inspection: Condition as new.

Conditioning: ≥3 days at indoor ambient conditions and ≥16 hours at 20±5°C & 50±20% rh.

Filling Material: A conventional urethane foam of nominal density 20-22kgm³ Ref: VP45, and an 85g thermally bonded polyester fibre wrap.

Test Procedure: As defined in Schedule 4 Part 1 of the above regulations.

Test Conditions: The test was conducted within the required conditions of 15-30°C & 20-70%rh.

RESULTS

Source No.	Application No.	Smoke/ Smoulder	Result - Ignition/ Non-Ignition
0	1	16min 42sec	PASS N/I
	2	17min 37sec	PASS N/I

COMMENTS

SCHEDULE 4 PART 1 MODIFICATION TO BS 5852: PART 1 THE CIGARETTE TEST	APP 1.	APP 2.
Both cigarettes were fully consumed within the stipulated 1 hour time period, however the cover and filling assembly continued to smoulder for greater than the stipulated 60min time period.	PASS N/I	PASS N/I
Progressive smouldering was established, the rate of smoulder was rapid, and the test was terminated before the stipulated time period.	PASS N/I	PASS N/I
Flames occurred though progressive smouldering, therefore the test was terminated before the stipulated 60min time period as it was deemed unsafe to continue.	PASS N/I	PASS N/I

CONCLUSION

This fabric sample Ref: PANDORA-AC-FR, passes the test specified in Schedule 4 Part 1 of The Furniture and Furnishings (Fire) (Safety) Regulations 1988 - Amended 1989, 1993 and 2010.



TECHNICAL REPORT

DESCRIPTION

Enquiry No: TFFLF89036

Item: One, Fabric – Ref: PANDORA-AC-FR

Supplied by: Interfabrics SI

The following test results relate only to the ignitability of the combination of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.

FURNITURE AND FURNISHINGS (FIRE) (SAFETY) REGULATIONS 1988 - AMENDED 1989, 1993 AND 2010 **SCHEDULE 5 PART 1 THE MATCH TEST (BASED ON BS 5852: 1979 PART 1)**

Initial Inspection: Condition as new.

Conditioning: ≥3 days at indoor ambient conditions and ≥16 hours at 20±5°C & 50±20% rh.

Test Procedure: As defined in Schedule 5 Part 1 of the above regulations using specified non fire-retardant polyurethane foam 20-22kg/m³.

Test Conditions: The test was conducted within the required conditions of 15-30°C & 20-70%rh.

RESULTS

Source No.	Application No.	Application Time	Flaming Time Following Removal of Source	Smoke/Smoulder	Result - Ignition/Non-Ignition
1	1	00min 20sec	00min 00sec	00min 15sec	PASS N/I
	2	00min 20sec	00min 00sec	00min 15sec	PASS N/I

COMMENTS

SCHEDULE 5 PART 1 THE MATCH TEST BASED ON BS 5852: 1979 PART 1 THE MATCH TEST	APP 1.	APP 2.
After removal of the ignition source the cover fabric melted open to expose the underlying filling material. The cover and filling assembly immediately ignited. The rate of fire development was rapid and the test was terminated before the stipulated 120sec time period as it was unsafe to continue.	PASS N/I	PASS N/I
After removal of the ignition source the cover fabric ignited, flames spread across the surface of the cover, leaving behind an intact char. The cover continued to burn for greater than the stipulated 120sec time period.	PASS N/I	PASS N/I
After removal of the ignition source the cover ignited, the cover char split and the underlying filling material ignited, the cover and filling assembly continued to burn for greater than the stipulated 120sec time period.	PASS N/I	PASS N/I
All flames ceased within the permitted 120sec, the test assembly continued to smoulder for greater than the stipulated 15min time period.	PASS N/I	PASS N/I

CONCLUSION

This fabric sample Ref: PANDORA-AC-FR, passes the test specified in Schedule 5 Part 1 of The Furniture and Furnishings (Fire) (Safety) Regulations 1988 - Amended 1989, 1993 and 2010.

Tested by: Vanessa Mitchell

Reported by: Luis Mitchell

Approved by: Stephen Cotton
Technical Specialist - Flammability

***** End of Report *****

